

# Multi-Size Pipe Flashing

## Standard & Silicone Roof Jack

Manufactured from EPDM or Silicon rubber, Roofjacks are compounded for maximum resistance to ozone, UV light & temperature extremes.

Flexible aluminum base will allow the flashing to conform to any metal roof configuration. Pipe location can be centered in the flat of the panel or the rib. Urethane sealant & self drilling screw complete the installation.

Roof jacks are well marked, so they can easily be cut with shears to fit the exactly the pipe size used.



	EPDM 500	SILICON
Advanced Ozone Resistance	70 hr @ 500 pphm	70 hr @ 500 pphm
High Temperature Intermittent Resistance	+ 275° F (+ 135° C)	+ 500° F (+ 260° C)
High Temperature Continuous Resistance	+ 212° F (+ 100° C)	+ 437° F (+ 225° C)
Low Temperature Resistance	- 65° F (- 55° C)	- 100° F (+ 74° C)

Mini	1/8" - 3/4" 3 mm to 20 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	1/16" 1/8" - 3/4" 2 1/4"	EPDM Silicon	7.50 N/A
#1	1/4" - 2" 6 mm to 50 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	Closed 1/4" - 2" 4 1/2"	EPDM Silicon	10.50 14.50
#2	1 1/4" - 3" 32 mm to 76 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	7/8" 1 1/4" - 3" 6"	EPDM Silicon	12.00 19.50
#3	1/4" - 4" 6 mm to 102 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	Closed 1/4" - 4" 8"	EPDM Silicon	13.50 22.50
#4	3" - 6" 76 mm to 152 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	2 1/2" 3" - 6" 10"	EPDM Silicon	23.00 37.00
#5	4" - 7" 102 mm to 178 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	3 1/2" 4" - 7" 11"	EPDM Silicon	24.00 47.00
#6	5" - 9" 127 mm to 228 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	4" 5" - 9" 12"	EPDM Silicon	26.00 49.50
#7	6" - 11" 152 mm to 280 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	5" 6" - 11" 14"	EPDM Silicon	36.00 75.00
#8	7" - 13" 178 mm to 330 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	6" 7" - 13" 17"	EPDM Silicon	48.00 108.00
#9	10" - 18" 254 mm to 467 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	8 1/2" 10" - 18" 25"	EPDM Silicon	78.00 156.00
Maxi	13" - 26" 330 mm to 660 mm	A-Top opening diameter B-Cut to suit pipe size C-Base Dimensions	11" 13" - 26" 34"	EPDM Silicon	95.00 200.00

Select and Trim...	Slide...	Form...	Seal...	Fasten...
Choose appropriate Master Flash with the opening at least 20% smaller than pipe diameter. If necessary trim opening to 20% smaller than pipe diameter.	Slide Master Flash down over pipe. (A non-petroleum base lubricant will ease installation.)	Press Master Flash down, bending it to conform to roof profile or roof irregularities. A blunt tool will help press flashing into tight roof angles	Apply sealant between base and roof.	Use fasteners to complete sealing. For UPC installation, fastener spacing may not exceed 1 1/2" (38 mm)
				